

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP4080LIXT

COMPATIBLE RADIOS	Motorola CP100d, CP185, CP476, CP477, CP1300, CP1600, CP1660, EP350, P140, P145, P160, P165, P180, P185
REPLACES OEM BATTERY	PMNN4080AR
COMPATIBLE CHARGERS	Endura EC1-MT18, EC1M-MT18, EC2M-MT18-D, EC6M-MT18, EC12M-MT18-D / Motorola PMLN5398, PMLN6597
VOLTAGE	7.4V
CAPACITY	2250 mAh / 16.7 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>300
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for cycle life or to maintain capacity)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (part number CL7144)
WARRANTY	12 months
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p>Dimensions (LxWxD) 4.68" x 2.15" x 0.90" 118.9 x 54.6 x 22.8 mm</p> <p>Weight 0.36 lbs. / 164 g</p> </div>