

<b>LMR BATTERY SPECIFICATIONS</b>	PART NUMBER
	<b>BP4468LI</b>

COMPATIBLE RADIOS	Motorola SL300, SL3500e, TLK100 / Vertex Standard EVX-S24 / fits SL7550, SL7550e, SL7580, SL7580e, SL7590, SL7590e with extended battery door (PMLN6745)
REPLACES OEM BATTERY	Motorola PMNN4468, PMNN4468A / Vertex Standard AAM01X001, FNB-V142LI
COMPATIBLE CHARGERS	Motorola PMLN7101, PMLN7109
VOLTAGE / CAPACITY	3.7V / 2300 mAh / 8.5 Wh (2200 mAh minimum)
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic UF553450Z or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for battery performance or cycle life)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL	ABS frame with label wrap
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO	