

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP4544LI

COMPATIBLE RADIOS	Motorola XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
REPLACES OEM BATTERY	PMNN4409, PMNN4544
COMPATIBLE CHARGERS	Endura EC1-MT16B, EC1M-MT16B, EC2M-MT16A-D, EC6M-MT16B, EC12M-MT16A-D / Logic LEVCA-MT16 / Motorola IMPRES WPLN4222, PMPN4284
VOLTAGE	7.2V
CAPACITY	2500 mAh / 18.0 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic UR1865ZM2 or equivalent
OPERATING TEMPERATURE	-10° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	500
CHARGING / CALIBRATION	Charges on IMPRES 1 and 2 chargers, but does not calibrate (calibration not required to maintain battery level icon on radio or low voltage warning)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP54 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CL7144)
WARRANTY	12 months
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p>Dimensions (HxWxD): 4.51" x 2.17" x 0.92" 114.5 mm x 55.1 mm x 23.3 mm).</p> </div>