

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPKNBL2LIP-34

COMPATIBLE RADIOS	Kenwood NX-5000, NX-5200, NX-5300, NX-5400, TK-5230, TK-5330, TK-5430, VP5230, VP5330, VP5430, VP6230, VP6330, VP6430, VP8000
REPLACES OEM BATTERY	KNB-L2M, KNB-L3M
RATINGS	IP67
COMPATIBLE CHARGERS	Endura EC1-KW4A, EC1M-KW4A, EC6M-KW4A, EC2M-KW4A-D, EC12M-KW4A-D/ EC2M-KW4B-D, EC12M-KW4B-D / EVC-KW4 / Kenwood KSC-32, KSC-52
VOLTAGE / CAPACITY	7.4V / 3400 mAh / 25.2 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Japanese cells
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Not required for cycle life
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP67 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 10px; margin-left: auto; margin-right: auto; width: fit-content;"> <p>Dimensions (H x W x D): 4.59" x 2.28" x 1.11" (116.5 x 57.9 x 28.2 mm)</p> <p>Weight: 0.4 lbs. / 181.4 g.</p> </div>