

| | |
|-----------------------------------|----------------------|
| LMR BATTERY SPECIFICATIONS | PART NUMBER |
| | BP232LIWP-L25 |

| | |
|------------------------|---|
| COMPATIBLE RADIOS | Icom IC-A14, IC-F14, IC-F15, IC-F24, IC-F25, IC-F33, IC-F34, IC-F43, IC-F43TR, IC-F44, IC-F3021, IC-F3023, IC-F3031, IC-F3101, IC-F3103, IC-F3161, IC-F3163, IC-F3230, IC-F3261, IC-F3263, IC-F3360, IC-F4021, IC-F4023, IC-F4031, IC-F4101, IC-F4103, IC-F4161, IC-F4163, IC-F4230, IC-F4261, IC-F4360, IC-F4263, IC-F4360 |
| REPLACES OEM BATTERY | BP-232WP |
| INGRES PROTECTION | IP68 rated |
| COMPATIBLE CHARGERS | Endura EC1-IC3B, EC1M-IC3B, EC6M-IC3B, EC2M-IC3-D, EC12M-IC3-D / Icom BC-160 |
| VOLTAGE / CAPACITY | 7.4V / 2500 mAh (18.5 Wh) |
| CHEMISTRY | Li-Ion |
| CELL TYPE | LG INR18650B4 or equivalent |
| OPERATING TEMPERATURE | -20° C to +60° C (discharge) / 0° C to +40° C (charge) |
| CHARGE CYCLES | >300 |
| CHARGE TYPE | Rapid |
| CONDITIONER COMPATIBLE | Yes (not required for battery performance or cycle life) |
| PROTECTION TYPES | Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact |
| HOUSING MATERIAL | ABS |
| HOUSING SEAL | Ultrasonic weld |
| METAL WELDING | Pure nickel tabs w/ spot welder |
| CLIP | N/A |
| WARRANTY | 12 months |
| PRODUCT PHOTO |  <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p>Dimensions (HxWxD): 3.62" x 2.21" x 0.84" 91.9 mm x 56.0 mm x 21.3 mm</p> <p>Weight 0.29 lbs. / 133.2 g</p> </div> |