

<b>LMR BATTERY SPECIFICATIONS</b>	PART NUMBER
	<b>BP284LI</b>

COMPATIBLE RADIOS	Icom IC-F3400D/DT/DS, IC-F3400DP/DPT/DPS, IC-F4400D/DT/DS, IC-F4400DP/DPT/DPS, IC-F7010T/S, IC-F7020, IC-F7020T/S, IC-F7040T/S
REPLACES OEM BATTERY	BP-284
COMPATIBLE CHARGERS	Endura EC1-IC8LI, EC1M-IC8LI, EC6M-IC8LI, EC2M-IC8LI-D, EC12M-IC8LI-D / Icom BC-219
VOLTAGE	7.2V
CAPACITY	3200 mAh / 23.0 Wh (3210 mAh typical, 3070 mAh minimum)
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic NCR18650B
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 10° C to +45° C (charge)
CHARGE CYCLES	300
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	N/A
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CLV113, not interchangeable with MB-133)
WARRANTY	12 months
PRODUCT PHOTO	