

|                                   |                   |
|-----------------------------------|-------------------|
| <b>LMR BATTERY SPECIFICATIONS</b> | PART NUMBER       |
|                                   | <b>BP4406LIIC</b> |

|                         |                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| COMPATIBLE RADIOS       | Motorola APX900, APX1000, APX2000, APX3000, APX4000, XPR3300, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801                                                                                                                                                    |
| REPLACES OEM BATTERY    | PMNN4406, PMNN4407, PMNN4491, NNTN8128                                                                                                                                                                                                                                                                                                                |
| COMPATIBLE CHARGERS     | Endura EC1-MT16B, EC1M-MT16B, EC2M-MT16A-D, EC6M-MT16B, EC12M-MT16A-D / EVC-MT16 / Motorola IMPRES WPLN4222, PMPN4283A, PMPN4527                                                                                                                                                                                                                      |
| VOLTAGE                 | 7.2V                                                                                                                                                                                                                                                                                                                                                  |
| CAPACITY                | 2000 mAh / 14.4 Wh                                                                                                                                                                                                                                                                                                                                    |
| CHEMISTRY / CELL TYPE   | Li-Ion / Panasonic NCA103450 or equivalent                                                                                                                                                                                                                                                                                                            |
| BATTERY TYPE            | Smart                                                                                                                                                                                                                                                                                                                                                 |
| OPERATING TEMPERATURE   | -20° C to +60° C (discharge) / 10° C to +45° C (charge)                                                                                                                                                                                                                                                                                               |
| CHARGE CYCLES           | 500                                                                                                                                                                                                                                                                                                                                                   |
| CHARGE TYPE             | Rapid                                                                                                                                                                                                                                                                                                                                                 |
| CONDITIONER COMPATIBLE  | Smart battery conditions on Motorola IMPRES chargers (conditioning not required for cycle life or battery run time)                                                                                                                                                                                                                                   |
| PROTECTION TYPES        | Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact                                                                                                                                                                                                                                                         |
| HOUSING MATERIAL / SEAL | ABS / ultrasonic weld                                                                                                                                                                                                                                                                                                                                 |
| INGRESS PROTECTION      | IP68 rated                                                                                                                                                                                                                                                                                                                                            |
| METAL WELDING           | Pure nickel tabs w/ spot welder                                                                                                                                                                                                                                                                                                                       |
| CLIP                    | Included (CL7144)                                                                                                                                                                                                                                                                                                                                     |
| WARRANTY                | 12 months                                                                                                                                                                                                                                                                                                                                             |
| PRODUCT PHOTO           | <div style="text-align: center;">  <div style="border: 1px dashed black; padding: 5px; margin-left: auto; margin-right: auto;"> <p><b>Dimensions (HxWxD):</b><br/>           4.51" x 2.18" x 0.71"<br/>           114.5 mm x 55.4 mm x 17.9 mm).</p> </div> </div> |