

<b>LMR BATTERY SPECIFICATIONS</b>	PART NUMBER
	<b>BP4409LI</b>

COMPATIBLE RADIOS	Motorola APX1000, APX3000, APX4000, XPR3300, XPR3500, XPR7350, XPR7550, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801
ALTERNATIVE TO	PMNN4409, PMNN4424AR, PMNN4544
VOLTAGE	7.4V
CAPACITY	2900 mAh / 21.5 Wh
CHEMISTRY / CELL TYPE	Li-Ion / LG INR18650MH1
OPERATING TEMPERATURE	-20° C ~ 60° C (discharge) / 0° C ~ 50° C (charge)
CHARGE CYCLES	>500
CHARGING / CALIBRATION	Charges on IMPRES 1 and 2 chargers, but does not calibrate (calibration not required to maintain semi-smart features)
BATTERY TYPE	Semi-smart (provides battery level icon on radio and low battery warning)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP67 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CL7144)
WARRANTY	12 months (capacity 80%)
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p><b>Dimensions (HxWxD):</b>            4.51" x 2.18" x 0.71"            114.5 mm x 55.4 mm x 17.9 mm</p> <p><b>Weight</b>            5.8 oz / 165.5 g</p> </div>