

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP5633LI

COMPATIBLE RADIOS	Kenwood NX-210, NX-410, NX-411, TK-2180, TK-3180, TK-5210, TK-5210G, TK-5310, TK-5310G, TK-5410
REPLACES OEM BATTERY	KNB-33L
COMPATIBLE CHARGERS	Endura EC1-KW4A, EC1M-KW4A, EC2M-KW4A-D, EC6M-KW4A, EC12M-KW4A-D / EVC-KW4, EVC-KW4-4 / Kenwood KSC-32
VOLTAGE	7.2V
CAPACITY	1900 mAh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic UF103450P or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (conditioning not required for cycle life or battery run time)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO	