

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP9009

COMPATIBLE RADIOS	Motorola HT750, HT1250, HT1550, PRO5150, PRO7150, PRO9150, GP320, GP340, GP360, GP380, GP640, GP680, GP1280, MTX850, MTX850LS, MTX900, MTX950, MTX8250LS, MTX9250
REPLACES OEM BATTERY	HNN9009AR
COMPATIBLE CHARGER / POD	Endura EC1-MT2, EC1M-MT2, EC2M-MT2-D, EC6M-MT2, EC12M-MT2-D / Motorola PMLN5197A, PMLN5197B
VOLTAGE	7.5V
CAPACITY	2000 mAh
CHEMISTRY	NiMH
CELL TYPE	Japanese (FDK HR-AAU or equivalent)
OPERATING TEMPERATURE	0° C to +50° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid or trickle
CONDITIONER COMPATIBLE	Yes
PROTECTION TYPES	Short circuit (with PTC) / over-charge (with NTC)
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included, length 3.09" / 78.5 mm (CL9008)
WARRANTY	12 months
PRODUCT PHOTO	 Dimensions (LxWxD) 4.85" x 2.20" x 0.77" 123.3 x 55.9 x 19.5 mm Weight 0.47 lbs. / 213 g