

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP9013LI

COMPATIBLE RADIOS	Motorola HT750, HT1250, HT1550, PRO5150, PRO7150, PRO9150, GP320, GP340, GP360, GP380, GP640, GP680, GP1280, MTX850, MTX850LS, MTX900, MTX950, MTX8250LS, MTX9250
ALTERNATIVE TO	HNN9013 / HNN9013DR
COMPATIBLE CHARGERS	Endura EC1-MT2, EC1M-MT2, EC2M-MT2-D, EC6M-MT2, EC12M-MT2-D / Motorola PMLN5197, WPLN4182
VOLTAGE	7.2V
CAPACITY	1800 mAh / 13.0 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Sanyo UF103450 or equivalent
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>300
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for battery run time or cycle life)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included
WARRANTY	12 months (capacity 80%)
PRODUCT PHOTO	