

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BP9858MHIC

COMPATIBLE RADIOS	Motorola XTS1500, XTS2250, XTS2500, MT1500, PR1500
REPLACES OEM BATTERY	NTN9858C (2100 mAh)
COMPATIBLE CHARGERS	Endura EC1-MT13B, EC1M-MT13B, EC2M-MT13-D, EC6M-MT13B, EC12M-MT13-D, EVC-MT13, EVC-MT13-4 / Motorola IMPRES 1 chargers (WPLN4114AR / WPLN4127AR) and IMPRES 2 chargers (PMPN4135A / PMPN4134A)
VOLTAGE	7.5V
CAPACITY	2500 mAh
CELL CHEMISTRY / TYPE	NiMH / FDK HR-AU or equivalent
BATTERY TYPE	Smart, charges and calibrates on IMPRES 1 and 2 chargers
OPERATING TEMPERATURE	-0° C to +50° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>450
CHARGE TYPE	Rapid or trickle
CONDITIONER COMPATIBLE	Yes
PROTECTION TYPES	Short circuit, over-discharge, over-temperature monitoring via charge contact
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welding
CLIP	Included (CL9008)
WARRANTY	12 months
PRODUCT PHOTO	 Dimensions (L x W x D) 4.84" x 2.32" x 0.98" 122.9 x 58.9 x 24.9 mm Weight 0.62 lbs. / 280.7 g