

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPBL2006LI

COMPATIBLE RADIOS	L3Harris HDP100, HDP150 / Hytera PD702, PD702G, PD702i, PD705, PD706, PD706G, PD708, PD752, PD752i, PD782, PD782G, PD782i, PD785, PD785G, PD786, PD786G, PD788, PD788G
ALTERNATIVE TO	BL2006 / BL2008 (Hytera) / HD-PA2V (Harris Momentum)
COMPATIBLE CHARGERS	Endura EC1-HY4, EC1M-HY4, EC6M-HY4, EC2M-HY4-D, EC12M-HY4-D / EVC-HY4 / Hytera CH20L06
VOLTAGE	7.4V
CAPACITY	2000 mAh / 14.8 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic NCA653864
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for cycle life or battery performance)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months (capacity 80%)
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; display: inline-block; margin-left: 20px;"> <p>Housing thickness 18 mm / 0.71"</p> </div>