

<b>LMR BATTERY SPECIFICATIONS</b>	PART NUMBER
	<b>BPTOPB500</b>

COMPATIBLE RADIOS	Tait Orca 5000 series / M/A-COM (Cougar / Panther) 400P, 405P, 600P, 605P, 625P
REPLACES OEM BATTERY	TOPB200
COMPATIBLE CHARGERS	Endura EC1-TA1, EC1M-TA1, EC6M-TA1 / Tait TOPA-CH-200, TOPA-CH-204, TOPA-CH-300, TOPA-CH-304 / ACT i20 with ITAI10BNN adapter
VOLTAGE	7.2V
CAPACITY	2150 mAh (typical) / 1950 mAh (minimum)
CHEMISTRY	NiMH
CELL TYPE	FDK HR-4/5AU
OPERATING TEMPERATURE	0° C to +50° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	450
CHARGE TYPE	Rapid or trickle / conditioner compatible
PROTECTION TYPES	Short circuit, over-discharge, over-temperature monitoring via charge contact
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CLTOPB500)
WARRANTY	12 months
PRODUCT PHOTO	