

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPU4409

COMPATIBLE RADIOS	Motorola APX1000, APX2000, APX3000, APX4000, XPR3300e, XPR3500, XPR3500e, XPR7350, XPR7350e, XPR7380, XPR7380e, XPR7550, XPR7550e, XPR7580, XPR7580e, DP4400, DP4401, DP4600, DP4601, DP4800, DP4801.
REPLACES OEM BATTERY	PMNN4409, PMNN4424AR, PMNN4544
COMPATIBLE CHARGERS	Endura EC1-MT16B, EC1M-MT16B, EC2M-MT16A-D, EC6M-MT16B, EC12M-MT16A-D / EVC-MT16, EVC-MT16-4 / Motorola IMPRES WPLN4222, PMPN4284
USB CHARGING	Internal circuitry allows charging with 24" USB cable included / status LED indicates charging, charge complete, or fault
VOLTAGE	7.4V
CAPACITY	2500 mAh / 19.2 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic UR18650ZY
OPERATING TEMPERATURE	-10° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>450
CHARGING / CALIBRATION	Yes (not required for cycle life or battery performance)
BATTERY TYPE	Smart (provides battery level icon on radio and low battery warning)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
WARRANTY	12 months (capacity 80%)
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p style="text-align: center;">Dimensions (HxWxD): 4.51" x 2.18" x 0.91" (14.5 mm x 55.4 mm x 23.1 mm).</p> </div>