

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPU9858

COMPATIBLE RADIOS	Motorola XTS1500, XTS2250, XTS2500, MT1500, PR1500
REPLACES OEM BATTERY	NNTN7335, NNTN7554, PMNN4495
COMPATIBLE CHARGERS	Endura EC1-MT13B, EC1M-MT13B, EC2M-MT13-D, EC6M-MT13B, EC12M-MT13-D / EVC-MT13 / Motorola NTN1667
USB CHARGING	Internal circuitry allows charging with 24" USB cable included / status LED indicates charging, charge complete, or fault
VOLTAGE	7.4V
CAPACITY	2500 mAh / 18.5 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic UR18650ZY or equivalent
OPERATING TEMPERATURE	-10° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>450
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for cycle life or battery performance)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via external charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld for housing
METAL WELDING	Pure nickel tabs w/ spot welding
CLIP	Included (CL9008)
WARRANTY	12 months
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p>Dimensions (L x W x D): 4.84" x 2.32" x 0.98" 122.9 x 58.9 x 24.9 mm</p> <p>Weight: 0.45 lbs. / 204.1 g</p> </div>