

LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPUKNBL2

COMPATIBLE RADIOS	Kenwood NX5000, NX5200, NX5300, NX5400, TK5230, TK5330, TK5430, VP5230, VP5330, VP5430, VP6230, VP6330, VP6430, VP8000
REPLACES OEM BATTERY	KNB-L1M, KNB-L2M
COMPATIBLE CHARGERS	Endura EC-KSC32, EC1-KW4A, EC12M-KW4C-D, EC1M-KW4A, EC2M-KW4C-D, EVC-KW4, EVC-KW4-4,
USB CHARGING	Internal circuitry allows charging with 24" USB cable included / status LED indicates charging, charge complete, or fault
VOLTAGE	7.4V
CAPACITY / ENERGY	2600 mAh / 19.2 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Panasonic UF103450P (Japanese)
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +40° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for battery run time or cycle life)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via external charge contact
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO	