

LMR BATTERY SPECIFICATIONS	PART NUMBER
	LEKNB40LIIS

COMPATIBLE RADIOS	Kenwood NX220, NX320, NX420, NX3200, NX3220, NX3300, NX3320, NX3400, nx3420, TK2140, TK2160, TK2170, TK2360, TK3140, TK3160, TK3170, TK3173, TK3360
REPLACES OEM BATTERY	KNB-40LCV, KNB-68LC
HAZ LOC RATINGS	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5th Edition standard for intrinsically safe use (Class I, II, III / Division 1 / Groups C-G / -20° C to 40° C, T3C) and non-incendive use (Class I, II, III / Division 2 / Groups A-G / -20° C to 40° C, T3C).
INGRESS PROTECTION	IP64 rated
COMPATIBLE CHARGERS	Endura EC1-KW3, EC1M-KW3, EC2M-KW3-D, EC6M-KW3, EC12M-KW3-D / Logic LEVCA-KW3 / Kenwood KSC-25
CONDITIONER COMPATIBLE	N/A
VOLTAGE / CAPACITY	7.4V / 1900 mAh / 14.1 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic NCA103450 (Japanese)
OPERATING TEMPERATURE	-20° C to +40° C (discharge, T3C) / 10° C to +45° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid
PROTECTION TYPES	Over charge / over discharge / over temperature
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO (Brand: Logic Energy)	 