

LMR BATTERY SPECIFICATIONS	PART NUMBER
	LEPA4MLIIS

COMPATIBLE RADIOS	Harris L3HARRIS XL-200Pi, XL-185Pi
REPLACES OEM BATTERY	XL-PA4M / 14035-5050-02
HAZ LOC RATINGS	Certified by SGS to TIA-4950 / UL 913 5th Edition standard for intrinsically safe use (Class I, II, III / Division 1 / Groups C-G / -20° C to 40° C, T3) and non-incendive use (Class I, II, III / Division 2 / Groups A-G / -20° C to 40° C, T3)
INGRESS PROTECTION	IP68 rated
COMPATIBLE CHARGERS	Endura EC1-HA3C, EC1M-HA3C, EC2M-HA3C-D, EC6M-HA3C, EC12M-HA3C-D / EVC-HA3C, EVC-HA3-4 / Harris XL-200Pi Single Bay Desktop
VOLTAGE / CAPACITY	7.2V / 5000 mAh / 36.0 Wh
CHEMISTRY / CELL TYPE	Li-Ion / Samsung INR21700-50E (Japanese)
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 10° C to +45° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months (capacity 80%)
PRODUCT PHOTO (Brand: Logic Energy)	 logic™ PN: LEPA4MLIIS CAUTION: DO NOT REMOVE OR RECHARGE BATTERY IN KNOWN HAZARDOUS AREA. DO NOT DISPOSE OF IN FIRE. ATTENTION: NE PAS ENLEVER NI RECHARGER CETTE PILE DANS UN ENDROIT DANGEREUX. NE PAS EXPOSER PRES DU FEU. Intrinsically Safe / Sécurité Intrinsèque CL I, II, III / Division 1 / Groups C-G / -20° to +40° C / T3. Non-incendive CL I, II, III / Division 2 / Groups A-G / -20° C to +40° C / T3. 7.2V / Li-Ion / 36 Wh 5000 mAh (4700 mAh min) MADE IN CHINA SGS 710297 RECYCLE 1-800-822-8821 Dimensions (HxWxD): 3.04" x 2.28" x 1.27" (77.3 x 57.9 x 32.3 mm) Weight 0.43 lbs. / 195 g