

LMR BATTERY SPECIFICATIONS	PART NUMBER
	PM234361LIP-45

COMPATIBLE RADIOS	L3Harris / Harris P5300, P5350, P5370, P5400, P5450, P5470, P5500, P5550, P5570, P7300, P7350, P7370, XG-15P, XG-25P, XG-75P, XL-45P, XL95P
ALTERNATIVE TO	BT-023436-001
COMPATIBLE CHARGERS	Endura EC1-HA1A, EC1M-HA1A, EC6M-HA1A, EC2M-HA1A-D, EC12M-HA1A-D / L3Harris CH-104560-007, 12082-0314-01
VOLTAGE	7.4V
CAPACITY	4500 mAh / 33.3 Wh
CHEMISTRY	LiPo
CELL TYPE	PolyMax™ HPC (AET 502-754698-4500)
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 20° C to +45° C (charge)
CHARGE CYCLES	400
CHARGE TYPE	Rapid
BATTERY TYPE	Yes (not required for battery run time or cycle life)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	Included (CL234065HT)
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 10px; margin-left: auto; margin-right: auto;"> <p>Dimensions (HxWxD): 4.52" x 2.44" x 1.01" 114.8 x 62.0 x 25.7 mm</p> </div>