



LMR BATTERY SPECIFICATIONS	PART NUMBER
	PMKNB43LIP

COMPATIBLE RADIOS	Kenwood NX-210, NX-210G, NX-410, NX-411, TK-2180, TK-3180, TK-5210, TK-5210G, TK-5310, TK-5310G, TK-5410
REPLACES OEM BATTERY	KNB-43L
COMPATIBLE CHARGERS	Endura EC1-KW4A, EC1M-KW4A, EC2M-KW4A-D, EC6M-KW4A, EC12M-KW4A-D, EVC-KW4 / Kenwood KSC-32
VOLTAGE	7.4V
CAPACITY	4100 mAh / 30.3 Wh
CHEMISTRY	LiPo
CELL TYPE	PolyMax HPC
OPERATING TEMPERATURE	-10° C to +50° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	500
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for battery run time or cycle life)
PROTECTION TYPES	Short circuit / over-charge / over-discharge / over-temperature monitoring via charge contact
HOUSING MATERIAL	ABS
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	24 months (capacity 80%) 24 months (materials and workmanship)
PRODUCT PHOTO	 PolyMax HPC™ Lithium Polymer • Maximum Energy