


LMR BATTERY SPECIFICATIONS	PART NUMBER
	BPPA3VLIXT

COMPATIBLE RADIOS	Harris XL-185P, XL-200P
ALTERNATIVE TO	Regular rate battery: XL-PA3V / 14035-4010-04 (3100 mAh)
COMPATIBLE CHARGERS	Endura EC1-HA3A, EC1M-HA3A, EC2M-HA3-D, EC6M-HA3A, EC12M-HA3-D / Harris XL-CH4X, XL-CH4W, XL-CH5A
VOLTAGE	7.2V
CAPACITY	Typical 5000 mAh / 36.0 Wh, minimum 4750 mAh / 34.2 Wh
CHEMISTRY	Li-Ion
CELL TYPE	Samsung INR21700-50E
OPERATING TEMPERATURE	-20° C to +60° C (discharge) / 0° C to +45° C (charge)
CHARGE CYCLES	500 (80% capacity at rated minimum, 76% capacity at rated typical)
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for cycle life or maintaining capacity)
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL / SEAL	PC / ultrasonic weld
INGRESS PROTECTION	IP68 rated
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	24 months
PRODUCT PHOTO	 <div style="border: 1px dashed black; padding: 5px; margin-left: 20px;"> <p>Dimensions 76.7 x 58.0 x 28.7 mm 3.02" x 2.28" x 1.13"</p> <p>Weight 189 g / 6.7 oz.</p> </div>