

LMR BATTERY SPECIFICATIONS	PART NUMBER
	LE232LIIS

COMPATIBLE RADIOS	Icom IC-F3161 (DT/T/DS/S), IC-F4161 (DT/D/DS/S)
REPLACES OEM BATTERY	BP-232FM (2000 mAh)
HAZ LOC RATING	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5th Edition standard for intrinsically safe use (Class I, II, III / Division 1 / Groups C-G / -20° C to 40° C, T3) and non-incendive use (Class I, II, III / Division 2 / Groups A-G / -20° C to 40° C, T3)
INGRES PROTECTION	IP68 rated
COMPATIBLE CHARGERS	Endura EC1-IC3B, EC1M-IC3B, EC6M-IC3B, EC2M-IC3-D, EC12M-IC3-D / Logic LEVCA-IC3 / Icom BC-160
VOLTAGE / CAPACITY	7.4V / 2500 mAh (18.5 Wh)
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic UR18650ZY
OPERATING TEMPERATURE	-20° C to +40° C (discharge, T3C) / 10° C to +45° C (charge)
CHARGE CYCLES	450
CHARGE TYPE	Rapid
CONDITIONER COMPATIBLE	Yes (not required for battery performance or cycle life)
PROTECTION TYPES	Over-charge / over-discharge / over-temperature
HOUSING MATERIAL	High impact ABS (AE8000)
HOUSING SEAL	Ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO	